

FASHION

SWITCH & SOCKET



PRICE LIST

ONLY FOR VIET NAM



COME FROM THE GERMAN THAT HAS LONG
CIVILIZATION AND FORERUNNER SCIENCE AND TECHNOLOGY





UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



V3.0

Series

V3.0

Come from the German that has long civilization and forerunner science and technology



V3.0PGK11-LS 19.000 VND

16A/250V
1 gang 1 way switch size L

V3.0PGK12-LS 29.000 VND

16A/250V
1 gang 2 way switch size L



V3.0PGK11-MS 18.000 VND

16A/250V
1 gang 1 way switch size M

V3.0PGK12-MS 28.000 VND

16A/250V
1 gang 2 way switch size M



V3.0PGK11-SS 16.000 VND

16A/250V
1 gang 1 way switch size S

V3.0-PGK12-SS 26.000 VND

16A/250V
1 gang 2 way switch size S



V3.0PGK31/L 36.000 VND

16A/250V
2 gang 1 way switch size M

V3.0PGK32/L 52.000 VND

16A/250V
2 gang 2 way switch size M



V3.0PGK20A 87.000 VND

20A/250V
20a switch size S



V3.0PGK/M 31.000 VND

Door bell switch Size M



V3.0DLR 35.000 VND

Red indicator light size S



V3.0DPGK/D 95.000 VND

Multi control switch size M



V3.0PCZ13/N-MS 56.000 VND

16A/250V
3 pole multi function socket size M



V3.0PCZ2/N-SS 36.000 VND

16A/250V
2 pole socket size S

V3.0

Come from the German that has long civilization and forerunner science and technology



V3.0P-TVMS

49.000 VND

Impedance : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size M



V3.0P-TVSS

49.000 VND

Impedance : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size S



V3.0P-TEMS

49.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Telephone socket size M



V3.0P-TELSS

49.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Telephone socket size S



V3.0P-PCMS

79.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Connecton mode T56BA, T568B
Computer socket size M



V3.0P-PCSS

79.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Connecton mode T56BA, T568B
Computer socket size S



V3.0P-D/G

98.000 VND

500W/220V~
only for filament lamp
Dimmer control



V3.0P-D/S

98.000 VND

Working voltage : 220V~ 50Hz
Load Power: 25-300W
Load can be connected : Ceiling fan
Speed control



V3.0USB

189.000 VND

Current : 2.1A
USB socket



V3.0-LMD

11.000 VND

Fill in the blank piece size L

**V3.0-PM1**Single panel with
bracket size S**19.000** VND**V3.0-PM2**Double panel with
bracket size 2S**19.000** VND**V3.0PM1.5**Middle panel with
bracket size M**19.000** VND**V3.0PM3**Triple panel with
bracket size L**19.000** VND**V3.0-C20-1**Single panel with
bracket**24.000** VND**V3.0-C20-2**Double panel with
bracket**24.000** VND**V3.0-C21**

C21 panel with bracket

24.000 VND**118F/C**

Waterproof box

90.000 VND**BOX/Y2**Concealed bottom box
100mm X 65mm X 50mm**24.000** VND

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



V7.0

Series

V7.0

Come from the German that has long civilization and forerunner science and technology



V7.0PGK11-LS 38.000 VND

16A/250V
1 gang 1 way switch size L

V7.0PGK12-LS 48.000 VND

16A/250V
1 gang 2 way switch size L



V7.0PGK11-MS 38.000 VND

16A/250V
1 gang 1 way switch size M

V7.0PGK12-MS 48.000 VND

16A/250V
1 gang 2 way switch size M



V7.0PGK11-SS 38.000 VND

16A/250V
1 gang 1 way switch size S

V7.0PGK12-SS 48.000 VND

16A/250V
1 gang 2 way switch size S



V7.0PGK31/L 59.000 VND

16A/250V
2 gang 1 way switch size M

V7.0PGK32/L 73.000 VND

16A/250V
2 gang 2 way switch size M



V7.0PGK20A 104.000 VND

20A/250V
20a switch size S



V7.0PGK/M 52.000 VND

16A/250V
Door bell switch Size M



V7.0DLR 55.000 VND

Red indicator light size S



V7.0PGK/D 125.000 VND

Multi control switch size M



V7.0PCZ13/N-MS 99.000 VND

16A/250V
3 pole multi function socket size M



V7.0PCZ2/N-SS 82.000 VND

16A/250V
2 pole socket size S

V7.0

Come from the German that has long oivilization and forerunner science and technology



V7.0P-TVMS

82.000 VND

Impedane : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size M



V7.0P-TVSS

82.000 VND

Impedane : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size S



V7.0P-TEAMS

101.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Telephone socket size M



V7.0P-TESS

101.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Telephone socket size S



V7.0P-PCMS

125.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Connecton mode T56BA,T568B
Computer socket size M



V7.0P-PCSS

125.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Connecton mode T56BA,T568B
Computer socket size S



V7.0P-D/G

135.000 VND

500W/220V~
only for filament lamp
Dimmer control



V7.0P-D/S

135.000 VND

Working voltage : 220V~ 50Hz
Load Power: 25-300W
Load can be connected : Ceiling fan
Speed control



V7.0USB

209.000 VND


Current : 2.1A
USB socket



V7.0-LMD

14.000 VND

Fill in the blank piece size L

**V7.0-PM1**Single panel with bracket
size S -Silver**64.000** VND**V7.0-PM1**Single panel with bracket
size S -Gold**64.000** VND**V7.0-PM2**Double panel with bracket size
2S- Silver**64.000** VND**V7.0-PM2**Double panel with bracket
size 2S-Gold**64.000** VND**V7.0-PM1.5**Middle panel with bracket
size M -Silver**64.000** VND**V7.0-PM1.5**Middle panel with bracket
size M -Gold**64.000** VND**V7.0-PM3**

Triple panel with bracket -Silver

64.000 VND**V7.0-PM3**

Triple panel with bracket -Gold

64.000 VND**V7.0-C21**

C21 panel with bracket

75.000 VND**V7.0-C20-1**

Single panel with bracket


75.000 VND**V7.0-C20-2**

Double panel with bracket

75.000 VND

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



V9.1

Series

V9.1

Come from the German that has long oivilization and forerunner science and technology



V9.1PGK11-LS 57.000 VND

16A/250V
1 gang 1 way switch size L

V9.1PGK12-LS 69.000 VND

16A/250V
1 gang 2 way switch size L



V9.1PGK11-MS 57.000 VND

16A/250V
1 gang 1 way switch size M

V9.1PGK12-MS 69.000 VND

16A/250V
1 gang 2 way switch size M



V9.1PGK11-SS 57.000 VND

16A/250V
1 gang 1 way switch size S

V9.1PGK12-SS 69.000 VND

16A/250V
1 gang 2 way switch size S



V9.1PGK31/L 88.000 VND

16A/250V
2 gang 1 way switch size M

V9.1PGK32/L 109.000 VND

16A/250V
2 gang 2 way switch size M



V9.1PGK20A 156.000 VND

20A/250V
20a switch size S



V9.1PGK/M 78.000 VND

Door bell switch Size M



V9.1DLR 82.000 VND

Red indictor light size S



V9.1PGK/D 188.000 VND

Multi control switch size M



V9.1PCZ13/N-MS 148.000 VND

16A/250V
3 pole multi funciton socket size M



V9.1PCZ2/N-SS 123.000 VND

16A/250V
2 pole socket size S

V9.1

Come from the German that has long civilization and forerunner science and technology



V9.1P-TVMS 123.000 VND

Impedance : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size M



V9.1P-TVSS 123.000 VND

Impedance : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size S



V9.1P-TELMS 151.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Telephone socket size M



V9.1P-TELSS 151.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Telephone socket size S



V9.1P-PCMS 187.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Connecton mode T56BA, T568B
Computer socket size M



V9.1P-PCSS 187.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIAB
Connecton mode T56BA, T568B
Computer socket size S



V9.1P-D/G 202.000 VND

500W/220V~
only for filament lamp
Dimmer control



V9.1P-D/S 202.000 VND

Working voltage : 220V~ 50Hz
Load Power: 25-300W
Load can be connected : Ceiling fan
Speed control



V9.1USB 280.000 VND

Current : 2.1A
USB socket



V9.1-LMD 20.000 VND

Fill in the blank piece size L

**V9.1-PM1**Single panel with bracket
size S -Silver**55.000** VND**V9.1-PM1**Single panel with bracket
size S -Gold**55.000** VND**V9.1-PM2**Double panel with
bracket -Silver**55.000** VND**V9.1-PM2**Double panel with
bracket -Gold**55.000** VND**V9.1-PM3**Triple panel with
bracket -Silver**55.000** VND**V9.1-PM3**Triple panel with
bracket -Gold**55.000** VND**V9.1-PM1.5**Middle panel with
bracket size M -Silver**55.000** VND**V9.1-PM1.5**Middle panel with
bracket size M -Gold**55.000** VND**V9.1-C20-2**

Double panel with bracket

65.000 VND**V9.1-C20-1**

Single panel with bracket

65.000 VND**V9.1-C21**

C21 panel with bracket

65.000 VND

UTEN

Noble and elegant, a symbol of nobles;
Fashionable and exquisite

V9.2

Series

V9.2

Come from the German that has long civilization and forerunner science and technology



V9.2-C20-1
Single panel with bracket

95.000 VND



V9.2-PM1
Single panel with bracket size S

85.000 VND



V9.2-C20-2
Double panel with bracket

95.000 VND



V9.2-PM2
Double panel with bracket size 2S

85.000 VND



V9.2-C21
C21 panel with bracket

95.000 VND



V9.2-PM1.5
Middle panel with bracket size M

85.000 VND



S-2Z13/N
16A/250V
2X3 pole multi function floor socket

980.000 VND



V9.2-PM3
Triple panel with bracket size L

85.000 VND



S-Z12/TEL/PC
Telephone+Computer
+2 pole floor socket

980.000 VND



S-TELPC
Telephone+Computer floor socket

980.000 VND

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



A8

Series

A8

Come from the German that has long civilization and forerunner science and technology



A8PGK11-LS

65.000 VND

16A/250V
1 gang 1 way switch size L

A8PGK12-LS

78.000 VND

16A/250V
1 gang 2 way switch size L



A8PGK11-MS

65.000 VND

16A/250V
1 gang 1 way switch size M

A8PGK12-MS

78.000 VND

16A/250V
1 gang 2 way switch size M



A8PGK11-SS

65.000 VND

16A/250V
1 gang 1 way switch size S

A8PGK12-SS

78.000 VND

16A/250V
1 gang 2 way switch size S



A8PGK31/L

99.000 VND

16A/250V
2 gang 1 way switch size M

A8PGK32/L

115.000 VND

16A/250V
2 gang 2 way switch size M



A8PGK20A

179.000 VND

20A/250V
20a switch size S



A8PGK/M

79.000 VND

Door bell switch Size M



A8DLR

95.000 VND

Red indicator light size S



A8DPGK/D

189.000 VND

Multi control switch size M



A8PCZ2/N-SS

141.000 VND

16A/250V
2 pole socket size S



A8PCZ13/N-MS

169.000 VND

16A/250V
3 pole multi function socket size M

A8

Come from the German that has long civilization and forerunner science and technology



A8P-TVSS

129.000 VND

Impedane : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size S



A8P-TVMS

129.000 VND

Impedane : 75Ω
Insertion loss: VHF 3.5 dB UHF<5dB
Flatness in Band ±1.0dB
Tivi socket size M



A8P-TELSS

159.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Telephone socket size S



A8P-TELMS

159.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Telephone socket size M



A8P-PCSS

195.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Connecton mode T56BA,T568B
Computer socket size S



A8P-PCMS

195.000 VND

Temperature: -20°C~70°C
Insulation resistance no less than 500MΩ
Electrical specification EIA/TIABI
Connecton mode T56BA,T568B
Computer socket size M



A8-D/G

215.000 VND

500W/220V~
only for filament lamp
Dimmer control



A8-D/S

215.000 VND

Working voltage : 220V~ 50Hz
Load Power: 25-300W
Load can be connected : Ceiling fan
Speed control



A8USB

279.000 VND

Current : 2.1A
USB socket



A8-LMD

15.000 VND

Fill in the blank piece size L

**A8-PM1**Single panel with
bracket size S**115.000 VND****A8PM1.5**Middle panel with
bracket size M**115.000 VND****A8-PM2**Double panel with
bracket size 2S**115.000 VND****A8PM3**Triple panel with
bracket size L**115.000 VND****A8-C20-1**Single panel with
bracket**125.000 VND****A8-C20-2**Double panel with
bracket**125.000 VND****A8-C21**

C21 panel with bracket

125.000 VND**TS-2Z13/N**

Table socket

880.000 VND

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



Q120B

Series

Q120B

Come from the German that has long civilization and forerunner science and technology



Q120B-K11 20.000 VND

16A/250V
1 gang 1 way switch size S

Q120B-K12 31.000 VND

16A/250V
1 gang 2 way switch size S



Q120B-K21 43.000 VND

16A/250V
2 gang 1 way switch size M

Q120B-K22 62.000 VND

16A/250V
2 gang 2 way switch size M



Q120B-K11D 89.000 VND

10A/250V
1 gang 1 way switch with LED size S

Q120B-K12D 109.000 VND

10A/250V
1 gang 2 way switch with LED size S



Q120B-KMLD 35.000 VND

16A/250V
Door bell switch with LED size S




Q120B-KML 95.000 VND

16A/250V
Door bell switch size S



Q120B-KCL 105.000 VND

16A/250V
intermediate switch
Curtain switch size S



Q120B-K13 115.000 VND

Intermediate switch size S



Q120B-K20A 120.000 VND

20A switch size size S



Q120B-Z13/N 67.000 VND

16A/250V
3 pole multi function socket



Q120B-Z12 45.000 VND

16A/250V
2 pole socket size

Q120B


Come from the German that has long civilization and forerunner science and technology



Q120B-USZ1

50.000 VND

15A/250V
Single US socket size S



Q120B-USZ2

110.000 VND

15A/250V
Double US socket size L



Q120B-D/S

118.000 VND

250W/220V
Speed control size S

Q120B-D/G

118.000 VND

300W/220V
Light dimmer



Q120B-2USB

225.000 VND

2.1A/5V
Double USB



Q120B-DH

215.000 VND

100W/220V
Motion sensor



Q120B-TV

58.000 VND

Impedance: 75Ω
Insertion loss: VHF3.5dB UHF<5dB
Flatness in Band±1.0dB
Tivi socket



Q120B-WTV

60.000 VND

Statellite socket



Q120B-TEL

58.000 VND

Insulation resistance: no less than 500MΩ
Electrical Specification: EIA/TIABI
Temperature: -20°C~70°C
Humidity: 95%
Telephone socket



Q120B-PC

94.000 VND

Insulation resistance: no less than 500MΩ
Electrical Specification: EIA/TIABI
Connection mode: T568A, T568B
Computer socket



Q120B-DLR

62.000 VND

Red indicator light

**Q120B-MD**

Bland board size S

4.000 VND**Q120B-MLKY**10W/220V
Electronic door bell**130.000** VND**Q120B-K45A**45A/25V
45A switch**210.000** VND**Q120B-PM1**Single panel with
bracket size S**23.000** VND**Q120B-PM2**Double panel with
bracket size 2S**23.000** VND**Q120B-PM3**

Triple panel with bracket size L

23.000 VND**Q120B-C20-1**

Single panel with bracket

29.000 VND**Q120B-C21**

C21 panel with bracket

29.000 VND**Q120B-C20-2**

Double panel with bracket

29.000 VND**Q120D-PM3**

Triple panel with bracket size L

70.000 VND

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



Q120

Series

Q120

Come from the German that has long civilization and forerunner science and technology



Q120-K11D 95.000 VND
10A/250V
1 gang 1 way switch with LED size S



Q120-K21 69.000 VND
16A/250V
2 gang 1 way switch size M

Q120-K22 79.000 VND
16A/250V
2 gang 2 way switch size M



Q120-K12D 115.000 VND
10A/250V
1 gang 2 way switch with LED size S



Q120-KMLD 78.000 VND
16A/250V
Door bell switch with LED size S



Q120-KML 103.000 VND
16A/250V
Door bell switch size S



Q120-KCL 188.000 VND
16A/250V
intermediate switch
Curtain switch size S



Q120-K13 188.000 VND
Intermediate switch size S



Q120-K20A 185.000 VND
20A switch size S



Q120-Z13/N 148.000 VND
16A/250V
3 pole multi function socket



Q120-Z12 123.000 VND
16A/250V
2 pole socket size

Q120


Come from the German that has long oivilization and forerunner science and technology



Q120-USZ1

135.000 VND

15A/250V
Single US socket size S



Q120-USZ2

235.000 VND

15A/250V
Double US socket size L



Q120-D/S

202.000 VND

250W/220V
Speed control size S

Q120-D/G

202.000 VND

300W/220V
Light dimmer



Q120-2USB

229.000 VND

2.1A/5V
Double USB



Q120-DH

345.000 VND

100W/220V
Motion sensor



Q120-TV

123.000 VND

Impedance:75Ω
Insertion loss: VHF3.5dB UHF<5dB
Flatness in Band±1.0dB
Tivi socket



Q120-WTV

145.000 VND

Statellite socket



Q120-TEL

151.000 VND

Insulation resistance: no less than 500MΩ
Electrical Specification: EIA/TIABI
Temperature:-20°C~70°C
Humidity:95%
Telephone socket



Q120-PC

187.000 VND

Insulation resistance: no less than 500MΩ
Electrical Specification: EIA/TIABI
Connection mode: T568A,T568B
Computer socket



Q120-DLR

62.000 VND

Red indictor light size S

**Q120-MD**

Bland board size S

6.500 VND**Q120-MLKY**10W/220V
Electronic door bell**245.000** VND**Q120-K45A**45A/25V
45A switch**225.000** VND**Q120-C-PM3**Triple PC panel with
stand- copper**70.000** VND**Q120-C-PM3**Triple PC panel with
stand- gold**70.000** VND**Q120-D-PM3**Triple PC panel with
stand- copper**70.000** VND**Q120-D-PM3**

Triple PC panel

70.000 VND**Q120D-C20-1**

Single panel with bracket

80.000 VND**Q120D-C20-2**

Double panel with bracket

80.000 VND**Q120D-C21**

C21 panel with bracket

80.000 VND

Q120


Come from the German that has long civilization and forerunner science and technology



Q120E-PM3

Triple glass panel with stand- white

235.000 VND



Q120E-PM3

Triple glass panel with stand- gold

235.000 VND



Q120E-PM3

Triple glass panel with stand- Wine

235.000 VND



Q120E-PM3

Triple glass panel with stand- Clouds

235.000 VND



Q120E-PM3

Triple glass panel with stand- Brown

235.000 VND



Q120E-PM3

Triple glass panel with stand- Black

235.000 VND



Q120E-C20-1

Single glass panel with bracket

245.000 VND



Q120E-C20-2

Double glass panel with bracket

245.000 VND



Q120E-C21

C21 glass panel with bracket

245.000 VND



FASHION

SWITCH & SOCKET



UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



V4.0

Series

V4.0

Come from the German that has long civilization and forerunner science and technology



V4.0GK11 **44.000 VND**

1 Gang 1 Way Switch

V4.0GK12 **51.000 VND**

1 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 40,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V4.0GK21 **64.000 VND**

2 Gang 1 Way Switch

V4.0GK22 **77.000 VND**

2 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 40,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V4.0GK31 **86.000 VND**

3 Gang 1 Way Switch

V4.0GK32 **104.000 VND**

3 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 40,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V4.0GK41 **106.000 VND**

4 Gang 1 Way Switch

V4.0GK42 **129.000 VND**

4 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 40,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V4.0GK11Z13/N **93.000 VND**

1 Gang 1 Way Switch
3 Pole Multi Function Socket

V4.0GK12Z13/N **100.000 VND**

1 Gang 2 Way Switch
3 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V4.0G1GM **62.000 VND**

Door Bell Switch

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 40,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V4.0GK13 **144.000 VND**

1 Gang Multi Control Switch

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 40,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V4.0GK23 **204.000 VND**

2 Gang Multi Control Switch

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 40,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V5.0GK20A **245.000 VND**

20A Switch

1. 20A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 10,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm



V5.0GK45A **295.000 VND**

45A Switch

1. 45A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Toggle: 10,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size:86mm × 86mm

V4.0

Come from the German that has long civilization and forerunner science and technology



V4.0GZ13/N

67.000 VND

3 Pole Multi Function Socket

- 1.16A/250VAC – 50/60HZ
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C,
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0GZ12Z13/N

109.000 VND

5 Pole Multi Function Socket

- 1.16A/250VAC --50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0G-2TV

131.000 VND

2 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0G-1TV

89.000 VND

1 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0G-2TEL

131.000 VND

2 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0G-1TEL

89.000 VND

1 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0G-2PC

189.000 VND

2 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0G-1PC

126.000 VND

1 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0-TVPC

168.000 VND

Tivi & Computer Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
- COMPUTER:
1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4.0-TVTEL

131.000 VND

Tivi & Telephone Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
- Telephone:
1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

**V4.0-TELPC****168.000 VND**

Telephone & Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size: 86mm × 86mm

**V4.0GZ13/2NU****490.000 VND**

USB Charging & Universal Socket

1. 2.1A/ 5V USB Charging
2. 16A/ 250V Universal Socket
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size: 86mm × 86mm

**V4.0G-1D/S****208.000 VND**

Speed Control Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: 25 ~ 300W
3. Minimum Starting Voltage: 90~110V
4. Load can be connected: Ceiling fan
5. Never connect the zero line
6. Plastics: PC - Box: 6 set - Carton: 60 set

Size: 86mm × 86mm

**V4.0G-1D/G****208.000 VND**

Dimmer Control Switch

1. Working Voltage: 220V ~ 50Hz
2. Maximum load power: 500W
3. Minimum Starting Voltage: 13~35V
4. Only for filament Lamp
5. Plastics: PC - Box: 6 set - Carton: 60 set

Size: 86mm × 86mm

**V4.0G-1D/Y****253.000 VND**

Sound Control Switch

1. Signal frequency range: 100Hz ~ 20KHz
2. Rated load impedance: 8Ω
3. Rated input power: 5W
4. Plastics: PC - Box: 6 set - Carton: 60 set

Size: 86mm × 86mm

**V5.0ZDC****890.000 VND**

Shaver Charging Socket

1. 10A ~ 16A
2. Load Power: 1100 ~ 2400W
3. Working Voltage: 110V ~ 220V
4. Plastics: PC - Box: 6 set - Carton: 60 set

Size: 86mm × 86mm

**V5.0G-1D/J****490.000 VND**

Insert Card for Power On

V5.0G-1D/JG**880.000 VND**Insert Card for Power On
(High frequency)

1. Working Voltage: 30A/220V
2. Only High-Frequency card insert into it can get power/Frequency: 13.56MHz
3. Other Card is useless on it
4. Plastics: PC - Box: 6 set - Carton: 60 set

Size: 86mm × 86mm

**V5.0G-3G/ML****413.000 VND**Don't Disturb & Please Clean
& Door bell Switch

1. Working Voltage: 220V ~ 50Hz
2. No Less than 500 MΩ
3. Maximum load power 5A
4. Plastics: PC - Box: 8 set - Carton: 80 set

Size: 86mm × 86mm

**V4.0G-1D/H****402.000 VND**

Human Body Sensor Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filament lamp 400W, fluorescent lamp, Electronic fluorescent lamp 200W
3. Delay time: 30 ~ 40s
4. Static Power: < 0.6W
5. Light sensitive environment: Daybreak/Nightfall/Evening
6. Range: Level angle 120°C
7. Plastics: PC - Box: 8 set - Carton: 80 set

Size: 86mm × 86mm

**V4.0-MD****33.000 VND**

Blank Panel

1. Blank Panel
2. Plastics: PC - Box: 20 set - Carton: 200 set

Size: 86mm × 86mm

V4.0

Come from the German that has long civilization and forerunner science and technology



V4.0G-1D/K 253.000 VND

Sound Control Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filamentlamp 400W, Fluorescent Lamps & LED Lamp 200W
3. Delay times: 60 ± 15s
4. Static Power: < 0.6W
5. Sensitivity: 60 ~ 80db
6. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm



V4.0G-1D/F 542.000 VND

Electronic Airflow Switch

1. Working Voltage: 220V ~ 50Hz
2. Maximum load power: 5A
3. Load Power: The motor
4. Electronic Airflow Switch
5. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm



V4.0G-1D/C 333.000 VND

Touch Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Current: 5A
3. Delay time: 30 ± 10s
4. Static Current < 70ua(rms)
5. Load Power: Filamentlamp, Fluorescent lamps, Electronic Fluorescentlamp
6. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm



V4.0-GK21 78.000 VND

2 Gang 1 Way Switch (Gold Border)

V4.0-GK22 91.000 VND

2 Gang 2 Way Switch (Gold Border)

1. Working Voltage: 16A ~ 250V
2. Gold Border
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4M/1M 26.000 VND

Switch Panel (Gold Border)

V4M/2M 26.000 VND

Switch Panel (Gold Border)

1. Switch Panel
2. Gold Border
3. Plastics: PC - Box: 5 set - Carton: 500 set

Size:86mm × 86mm



V4.0-GZ12Z13/N 123.000 VND

5 Pole Multi Function Socket (Gold Border)

1. Working Voltage: 16A ~ 250V
2. Gold Border
4. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V4M/1M 26.000 VND

Switch Panel (Silver Border)

V4M/2M 26.000 VND

Switch Panel (Silver Border)

1. Switch Panel
2. Silver Border
3. Plastics: PC - Box: 5 set - Carton: 500 set

Size:86mm × 86mm



UBBOX/A 24.000 VND

Cassee Box

1. Plastics: PC - Carton: 100 set

Size:85mm × 85mm × 50mm



UB1F/C 90.000 VND

Waterproof Box

1. Waterproof
2. Plastics: PC - Box: 1 set - Carton: 200 set

UTEN

Noble and elegant, a symbol of nobles;
Fashionable and exquisite



V6.0

Series

V6.0

Come from the German that has long civilization and forerunner science and technology



V6.0GK11 **111.000 VND**

1 Gang 1 Way Switch

V6.0GK12 **119.000 VND**

1 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK21 **131.000 VND**

2 Gang 1 Way Switch

V6.0GK22 **144.000 VND**

2 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK31 **151.000 VND**

3 Gang 1 Way Switch

V6.0GK32 **169.000 VND**

3 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK41 **171.000 VND**

4 Gang 1 Way Switch

V6.0GK42 **195.000 VND**

4 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK11Z13/N **149.000 VND**

1 Gang 1 Way Switch
3 Pole Multi Function Socket

V6.0GK12Z13/N **155.000 VND**

1 Gang 2 Way Switch
3 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times / Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0G1GM **126.000 VND**

Door Bell Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK13 **189.000 VND**

1 Gang Multi Control Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK23 **289.000 VND**

2 Gang Multi Control Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK20A **295.000 VND**

20A Switch

1. 20A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



V6.0GK45A **345.000 VND**

45A Switch

1. 45A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

**V6.0GZ13/N****129.000 VND**

3 Pole Multi Function Socket

- 1.16A/250VAC -- 50/60Hz
 2. Copper Class: Phosphor Bronze
 3. Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C,
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0GZ12Z13/N****144.000 VND**

5 Pole Multi Function Socket

- 1.16A/250VAC -- 50/60Hz
 2. Copper Class: Phosphor Bronze
 3. Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0G-1TV****153.000 VND**

1 Tivi Socket

1. Impedance: 75 Ω
 2. Insertion Loss: VHF < 3.5dB
 - UHF < 5dB, Flatness in band ±1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0G-2TV****186.000 VND**

2 Tivi Socket

1. Impedance: 75 Ω
 2. Insertion Loss: VHF < 3.5dB
 - UHF < 5dB, Flatness in band ±1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0G-1TEL****153.000 VND**

1 Telephone Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0G-2TEL****186.000 VND**

2 Telephone Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0G-1PC****204.000 VND**

1 Computer Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0G-2PC****279.000 VND**

2 Computer Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0-TVPC****242.000 VND**

Tivi & Computer Socket

1. Impedance: 75 Ω
 2. Insertion Loss: VHF < 3.5dB
 - UHF < 5dB, Flatness in band ±1.0 dB
 - COMPUTER:
 1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

**V6.0-TVTEL****186.000 VND**

Tivi & Telephone Socket

1. Impedance: 75 Ω
 2. Insertion Loss: VHF < 3.5dB
 - UHF < 5dB, Flatness in band ±1.0 dB
 - Telephone:
 1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

V6.0

Come from the German that has long civilization and forerunner science and technology



V6.0-TELPC 242.000 VND

Telephone & Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500m\Omega$
3. Electrical Specification: ELA/TIABI
1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500m\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V6.0G-1D/S 246.000 VND

Speed Control Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: 25 ~ 300W
3. Minimum Starting Voltage: 90~110V
4. Load can be connected: Ceiling fan
5. Never connect the zero line
6. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm × 86mm



V6.0G-1D/G 246.000 VND

Dimmer Control Switch

1. Working Voltage: 220V ~ 50Hz
2. Maximum load power: 500W
3. Minimum Starting Voltage: 13~35V
4. Only for filament Lamp
5. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm × 86mm



V6.0G-1D/Y 266.000 VND

Sound Control Switch

1. Signal frequency range: 100Hz ~ 20KHz
2. Rated load impedance: 8Ω
3. Rated input power: 5W
4. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm × 86mm



V6.0GZ13/2NU 540.000 VND

USB Charging & Universal Socket

1. 2.1A/ 5V USB Charging
2. 16A/ 250V Universal Socket
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V6.0ZDC 945.000 VND

Shaver Charging Socket

1. 10A ~ 16A
2. Load Power: 1100 ~ 2400W
3. Working Voltage: 110V ~ 220V
4. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm × 86mm



V6.0G-1D/J 590.000 VND

Insert Card for Power On

1. Working Voltage: 30A/220V
2. Plastics: PC - Box: 6 set - Carton: 60 set

V6.0G-1D/JG 980.000 VND

Insert Card for Power On
(High frequency)

1. Working Voltage: 30A/220V
2. Only High-Frequency card insert into it can get power/Frequency: 13.56MHz
3. Other Card is useless on it
4. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm × 86mm



V6.0G-1D/F 622.000 VND

Electronic airflow switch

1. Working Voltage: 220V ~ 50Hz
2. Maximum Load Power: 25 ~ 300W
3. Load can be connected: Ceiling fan
4. Minimum Starting Voltage: 90 ~ 110V
5. Electronic Airflow Switch
6. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm



V6.0G-MD 99.000 VND

Blank Panel

1. Blank Panel
2. Plastics: PC - Box: 20 set - Carton: 200 set

Size:86mm × 86mm



V6.0G-UH 780.000 VND

USB & HDMI

1. 2.1A/ 5V USB Charging
2. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm

**V6.0G-1D/C****348.000 VND**

Touch Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Current: 5A
3. Delay time: 30 ± 10s
4. Static Current: ≤ 70UA(RMS)
5. Load Power: Filament lamp, Fluorescent lamps, Electronic Fluorescent lamp
6. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**V6.0G-3G/ML****590.000 VND**Don't Disturb & Please Clean
& Door bell Switch

1. Working Voltage: 220V ~ 50Hz
2. No Less than 500 MΩ
3. Maximum load power 5A
4. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**V6.0G-1D/H****399.000 VND**

Human Body Sensor Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filament lamp 400W, fluorescent lamp, Electronic fluorescent lamp 200W
3. Delay time: 30 ~ 40s
4. Static Power: < 0.6W
5. Light sensitive environment: Daybreak/Nightfall/Evening
6. Range: Level angle 120°C
7. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**V6.0DPGK22****280.000 VND**2 Gang Switch
& with Please Clean
& Do not disturb

1. Working Voltage: 16A/250V
2. 1 Gang Please Clean Switch
3. 1 Gang Do not disturb Switch
4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

**V6.0-A/S****485.000 VND**

Step light

1. It is a light with sensor which you can install in the stair or corridor.
2. This light is influenced by the ambient light sense, and it will automatically sense the ambient light sense to decide whether to turn it on or not.
3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

**V6.0G-1D/K****277.000 VND**

Sound Control Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filament lamp 400W, Fluorescent Lamps & LED Lamp 200W
3. Delay times: 60 ± 15s
4. Static Power: < 0.6W
5. Sensitivity: 60 ~ 80db
6. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**V6.0KZ12Z13/N****186.000 VND**

1 Gang & Universal Socket

1. 16A/250VAC -- 50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

**V6.0-F/L****16.000 VND**

SOS Emergency Switch

- Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

**S2Z13/N****980.000 VND**Floor Socket
& Pole Multi Function Socket

1. 16A/250V Floor Socket
2. 2x3 Pole multi Function Socket
3. Plastics: PC - Box: 1 set - Carton: 20 set

**SZ12/TEL/PC****980.000 VND**2 Pole Socket & TEL Socket
& PC Socket

1. 2 Pole Socket
2. TEL Socket
3. PC Socket
4. Plastics: PC - Box: 1 set - Carton: 20 set

V6.0

Come from the German that has long oivilization and forerunner science and technology



V6.1-M/2M

243.000 VND

Double Panel with bracket

Plastics: PC - Box: 6 set - Carton: 84 set
Size: 172mm x 86mm



V6.1-M/3M

425.000 VND

Triple Panel with bracket

Plastics: PC - Box: 6 set - Carton: 84 set
Size: 258mm x 86mm



V6.1-M/4M

663.000 VND

Quadruple Panel with bracket
Size: 344mm x 86mm



V6.1-M/5M

782.000 VND

Quintuple Panel with bracket
Size: 430mm x 86mm



UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



Q7

Series

Q7 Come from the German that has long civilization and forerunner science and technology



Q7GK12 203.000 VND

1 Gang 2 Way Switch LED

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK22 293.000 VND

2 Gang 2 Way Switch LED

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK32 380.000 VND

3 Gang 2 Way Switch LED

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK42 484.000 VND

4 Gang 2 Way Switch LED

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK12Z13/N 250.000 VND

1 Gang 2 Way Switch
3 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7-GM 145.000 VND

Door Bell Switch LED

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK13 245.000 VND

1 Gang Multi Control Switch LED

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK23 300.000 VND

2 Gang Multi Control Switch LED

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK20A 335.000 VND

20A Switch

1. 20A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm



Q7GK45A 399.000 VND

45A Switch

1. 45A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7GZ13/N 148.000 VND
3 Pole Multi Function Socket

- 1.16A/250VAC -- 50/60Hz
 2. Copper Class: Phosphor Bronze
 3. Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C,
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7GZ12Z13/N 168.000 VND
5 Pole Multi Function Socket

- 1.16A/250VAC -- 50/60Hz
 2. Copper Class: Phosphor Bronze
 3. Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C,
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7-MD 113.000 VND
Blank Panel

1. Blank Panel
 2. Plastics: PC - Box: 20 set - Carton: 200 set
- Size:86mm × 86mm


Q7GK11Z12Z13/N 269.000 VND
1 Gang 1 Way Switch Led & 5 Pins Universal Socket

1. 1 Gang 2 way Switch
 2. 5 Pins Universal Socket
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7G-1TEL 175.000 VND
1 Telephone Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7G-2TEL 214.000 VND
2 Telephone Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7G-1TV 175.000 VND
1 Tivi Socket

1. Impedance: 75 Ω
 2. Insertion Loss: VHF<3.5dB
UHF < 5dB, Flatness in band $\pm 1.0\text{ dB}$
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7G-2TV 214.000 VND
2 Tivi Socket

1. Impedance: 75 Ω
 2. Insertion Loss: VHF<3.5dB
UHF < 5dB, Flatness in band $\pm 1.0\text{ dB}$
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7G-1PC 234.000 VND
1 Computer Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm


Q7G-2PC 320.000 VND
2 Computer Socket

1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm × 86mm

Q7 Come from the German that has long oivilization and forerunner science and technology



Q7-TVPC

278.000 VND

Tivi & Computer Socket

- TV :
1. Lmpedance: 75 Ω
 2. Insertion Loss: VHF3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- COMPUTER:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500m\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



Q7-TELPC

278.000 VND

Telephone & Computer Socket

- Telephone:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500m\Omega$
 3. Electrical Specification: ELA/TIABI
- Computer
1. Insertion Resistance: $\geq 500m\Omega$
 2. Electrical Specification: ELA/TIABI
 3. Connection Mode: T568A, T568B
 4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



Q7-TVTEL

213.000 VND

TV & Telephone Socket

- TV :
1. Lmpedance: 75 Ω
 2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Telephone:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500m\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



Q7G-1Y/C

176.000 VND

1 Gang Sound & 1 Way loud Speaker

1. Wire terminals composite structures, can meet the speaker different connection ways
 2. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



Q7G-1D/S

282.000 VND

Speed Control Switch

1. Sigah frequency range: 100Hz ~ 20KHz
 2. Rated load umpedance: 8 Ω
 3. Rated input power: 5W
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm $\times$ 86mm



Q7G-1D/G

282.000 VND

Dimmer Control Switch

1. Working Voltage: 220V ~ 50Hz
 2. Maximum load power: 500W
 3. Minimum Staring Voltage: 13~35V
 4. Only for filament Lamp
 5. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm $\times$ 86mm



Q7G-1D/Y

305.000 VND

Sound Control Switch

1. Sigah frequency range: 100Hz ~ 20KHz
 2. Rated load umpedance: 8 Ω
 3. Rated input power: 5W
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm $\times$ 86mm



Q7GZ13/2NU

560.000 VND

USB Charging & Universal Socket

1. 2.1A/ 5V USB Charging
 2. 16A/ 250V Universal Socket
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



Q7G-1D/J

678.000 VND

Insert Card for Power On

1. Working Voltage: 30A/220V
2. Plastics: PC - Box: 6 set - Carton: 60 set

Q7G-1D/JG

995.000 VND

Insert Card for Power On
(High frequency)

1. Working Voltage: 30A/220V
 2. Only High-Frequency card insert into it can get power/Frequency: 13.56MHz
 3. Other Card is useless on it
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm $\times$ 86mm



Q7G-3G/ML

678.000 VND

Don't Disturb & Please Clean
& Door bell Switch

1. Working Voltage: 220V ~ 50Hz
 2. No Less than 500 M Ω
 3. Maximum load power 5A
 4. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm $\times$ 86mm


Q7DPGK22 380.000 VND

2 Gang Switch & with Please Clean
& Do not disturb

1. Working Voltage: 16A/250V
2. 1 Gang Please Clean Switch
3. 1 Gang Do not disturb Switch
4. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm


Q7G-1D/H 458.000 VND

Human Body Sensor Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filament lamp 400W, fluorescent lamp, Electronic fluorescent lamp 200W
3. Delay time: 30 ~ 40s
4. Static Power: < 0.6W
5. Light sensitive environment: Daybreak/Nightfall/Evening
6. Range: Level angle 120°C
7. Plastics: PC - Box: 8 set - Carton: 80 set
Size: 86mm × 86mm


Q7ZDC 1.086.000 VND

Shaver Charging Socket

1. 10A ~ 16A
2. Load Power: 1100 ~ 2400W
3. Working Voltage: 110V ~ 220V
4. Plastics: PC - Box: 6 set - Carton: 60 set
Size: 86mm × 86mm


Q7G-1D/C 400.000 VND

Touch Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Current: 5A
3. Delay time: 30 ± 10s
4. Static Current ≤ 70UA(RMS)
5. Load Power: Filament lamp, Fluorescent lamp, Electronic Fluorescent lamp
6. Plastics: PC - Box: 8 set - Carton: 80 set
Size: 86mm × 86mm


Q7G-1D/F 715.000 VND

Electronic Airflow Switch

1. Working Voltage: 220V ~ 50Hz
2. Maximum load power: 5A
3. Load Power: The motor
4. Electronic Airflow Switch
5. Plastics: PC - Box: 8 set - Carton: 80 set
Size: 86mm × 86mm


Q7G-1D/K 318.000 VND

Sound Control Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filament lamp 400W, Fluorescent Lamps & LED Lamp 200W
3. Delay times: 60 ± 15s
4. Static Power: < 0.6W
5. Sensitivity: 60 ~ 80dB
6. Plastics: PC - Box: 8 set - Carton: 80 set
Size: 86mm × 86mm


UB1F/C 90.000 VND

Waterproof Box

1. Waterproof
2. Plastics: PC - Box: 1 set - Carton: 200 set


UBBOX/A 24.000 VND

Cassee Box

1. Plastics: PC - Carton: 100 set
Size: 85mm × 85mm × 50mm

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



Q9

Series

Q9

Come from the German that has long civilization and forerunner science and technology



Q9GK12

215.000 VND

1 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GK22

306.000 VND

2 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GK32

396.000 VND

3 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GK42

490.000 VND

4 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GKZ12Z13/N

328.000 VND

5 Pole Multi Function Socket With Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9G1GM

223.000 VND

Door Bell Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GK13

306.000 VND

1 Gang Multi Control Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GK23

415.000 VND

2 Gang Multi Control Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GK20A

355.000 VND

20A Switch

1. 20A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9GK45A

415.000 VND

45A Switch

1. 45A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

Q9 Come from the German that has long oivilization and forerunner science and technology



Q9-MD 194.000 VND

Blank Panel

1. Blank Panel
2. Plastics: PC - Box: 20 set - Carton: 200 set
- Size: 86mm × 86mm



Q9GZ12Z13/N 274.000 VND

S Pole Multi Function Socket

1. 16A/250VAC ~ 50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C, ...
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9G-1TEL 274.000 VND

1 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9G-2TEL 356.000 VND

2 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9G-1TV 274.000 VND

1 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
- UHF < 5dB, Flatness in band ±1.0 dB
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9G-2TV 356.000 VND

2 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
- UHF < 5dB, Flatness in band ±1.0 dB
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9G-1PC 338.000 VND

1 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9G-2PC 468.000 VND

2 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



Q9-TVPC 385.000 VND

1ITVI & Computer Socket

- TV :
1. Impedance: 75 Ω
 2. Insertion Loss: VHF 3.5dB
 - UHF < 5dB, Flatness in band ±1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- COMPUTER:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
 - Size: 86mm × 86mm



Q9-TELPC 385.000 VND

Telephone & Computer Socket

- Telephone:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: ≥ 500mΩ
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
 - Size: 86mm × 86mm


Q9-TVTEL 338.000 VND

Tivi & Telephone Socket

TV :

1. Impedance: 75 Ω
 2. Insertion Loss: VHF<3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Telephone:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500m\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm $\times$ 86mm


Q9G-1Y/C 317.000 VND

1 Gang Sound & 1 Way loud Speaker

1. Wire terminals composite structures, can meet the speaker different connection ways
 2. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm $\times$ 86mm


Q9GZ13/2NU 806.000 VND

USB Charging & Universal Socket

1. 2.1A/ 5V USB Charging
 2. 16A/ 250V Universal Socket
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size:86mm $\times$ 86mm


Q9G-1D/S 438.000 VND

Speed Control Switch

1. Working Voltage: 220V ~ 50Hz
 2. Load Power: 25 ~ 300W
 3. Minimum Starting Voltage: 90~110V
 4. Load can be connected: Ceiling fan
 5. Never connect the zero line
 6. Plastics: PC - Box: 6 set - Carton: 60 set
- Size:86mm $\times$ 86mm


Q9G-1D/G 438.000 VND

Dimmer Control Switch

1. Working Voltage: 220V ~ 50Hz
 2. Maximum load power: 500W
 3. Minimum Starting Voltage: 13~35V
 4. Only for filament Lamp
 5. Plastics: PC - Box: 6 set - Carton: 60 set
- Size:86mm $\times$ 86mm


Q9G-1D/Y 486.000 VND

Door bell switch Size M

1. Signal frequency range: 100Hz ~ 20KHz
 2. Rated load impedance: 8 Ω
 3. Rated input power: 5W
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size:86mm $\times$ 86mm


Q9GZDC 1.428.000 VND

Shaver Charging Socket

1. 10A ~ 16A
 2. Load Power: 1100 ~ 2400W
 3. Working Voltage: 110V ~ 220V
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size:86mm $\times$ 86mm


Q9G-3G/ML 840.000 VND

Don't Disturb & Please Clean & Door bell Switch

1. Working Voltage: 220V ~ 50Hz
 2. No Less than 500 M Ω
 3. Maximum load power 5A
 4. Plastics: PC - Box: 8 set - Carton: 80 set
- Size:86mm $\times$ 86mm


Q9G-1D/J 1.366.000 VND

Insert Card for Power On

1. Working Voltage: 30A/220V
 2. Plastics: PC - Box: 6 set - Carton: 60 set
- Size:86mm $\times$ 86mm


Q9G-1D/JG 1.666.000 VND

Insert Card for Power On (High frequency)

1. Working Voltage: 30A/220V
 2. Only High-Frequency card insert into it can get power/Frequency: 13.56MHz
 3. Other Card is useless on it
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size:86mm $\times$ 86mm

Q9 Come from the German that has long civilization and forerunner science and technology



Q9G-1D/C 734.000 VND

Touch Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Current: 5A
3. Delay time: 30 ± 10s
4. Static Current ≤ 70UA(RMS)
5. Load Power: Filamentlamp, Fluorescentlamps, Electronic Fluorescentlamp
6. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm



Q9G-1D/H 890.000 VND

Human Body Sensor Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filamentlamp 400W, fluorescentlamp, Electronic fluorescentlamp 200W
3. Delay time: 30 ~ 40s
4. Static Power: < 0.6W
5. Light sensitive environment: Daybreak/Nightfall/Evening
6. Range: Level angle 120°C
7. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm



Q9G-1D/K 510.000 VND

Sound Control Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filamentlamp 400W, Fluorescent Lamps & LED Lamp 200W
3. Delay times: 60 ± 15s
4. Static Power: < 0.6W
5. Sensitivity: 60 ~ 80db
6. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm × 86mm



Q9A/S 695.000 VND

Step light

1. It is a light with sensor which you can install in the stair or corridor.
2. This light is influenced by the ambient light sense, and it will automatically sense the ambient light sense to decide whether to turn it on or not.
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



V6G-W/F 1.365.000 VND

Multifunctional Wall WiFi Router

1. Working Voltage: 110 ~ 240V
2. Starting Voltage: 5V 1500mA from USB Socket
3. USB Socket can connect with U Disk, Mobile hard disk.
4. WPS and WiFi design makes it easy to encrypt data and turn WiFi signals on and off.
5. Effectively reduce signal blind area, extend WiFi distance and save a lot of network wiring.
6. Charge LAN Power, it makes Network connection is optional.
7. Support 3G SIM card.

Size:86mm × 86mm



Q9G-F/L 551.000 VND

SOS Emergency Switch

1. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm



Q9G-M/2M 89.000 VND

Double Panel with bracket

1. Plastics: PC - Box: 6 set - Carton: 84 set

Size:147mm × 90mm



Q9-M/3M 129.000 VND

Triple Panel with bracket

1. Plastics: PC - Box: 6 set - Carton: 84 set

Size:260mm × 90mm



Q9-M/4M 169.000 VND

Quadruple Panel with bracket

Size:346mm × 90mm



Q9-M/5M 219.000 VND

Quintuple Panel with bracket

Size:432mm × 90mm

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



A5

Series

A5

Come from the German that has long civilization and forerunner science and technology



A5GK11 169.000 VND

1 Gang 1 Way Switch

A5GK12 180.000 VND

1 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5GK21 196.000 VND

2 Gang 1 Way Switch

A5GK22 211.000 VND

2 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5GK31 221.000 VND

3 Gang 1 Way Switch

A5GK32 245.000 VND

3 Gang 2 Way Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5GK41 248.000 VND

4 Gang 1 Way Switch

A5GK42 279.000 VND

4 Gang 2 Way Switch


1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5G-1GM 190.000 VND

Door Bell Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5GK13 238.000 VND

1 Gang Multi Control Switch

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5-MD 155.000 VND

Blank Panel

1. Blank Panel
 2. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5GZ13/N 190.000 VND

3 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
 2. Copper Class: Phosphor Bronze
 3. Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



A5GZ13/2NU 620.000 VND

USB Charging & Universal Socket

1. 2.1A/ 5V USB Charging
2. 16A/ 250V Universal Socket
3. Plastics: PC - Box: 10 set - Carton: 100 set



A5GZ12Z13/N 199.000 VND

5 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set

**A5G-1D/S****338.000 VND****Speed Control Switch**

1. Working Voltage: 220V ~ 50Hz
2. Load Power: 25 ~ 300W
3. Minimum Starting Voltage: 90~110V
4. Load can be connected: Ceiling fan
5. Never connect the zero line
6. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm × 86mm

**A5G-1D/G****338.000 VND****Dimmer Control Switch**

1. Working Voltage: 220V ~ 50Hz
2. Maximum load power: 500W
3. Minimum Starting Voltage: 13~35V
4. Only for filament Lamp
5. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm × 86mm

**A5GK11Z13/N****218.000 VND****1 Gang 1 Way Switch
3 Pole Multi Function Socket****A5GK12Z13/N****228.000 VND****1 Gang 2 Way Switch
3 Pole Multi Function Socket**

1. 16A/250VAC -- 50/60Hz
2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
4. Working Temperature: -20°C~ 70°C.
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

**A5G-1TEL****223.000 VND****1 Telephone Socket**

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

**A5G-2TEL****263.000 VND****2 Telephone Socket**

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

**A5G-1TV****223.000 VND****1 Tivi Socket**

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

**A5G-2TV****263.000 VND****2 Tivi Socket**

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

**A5G-1PC****287.000 VND****1 Computer Socket**

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

**A5G-2PC****373.000 VND****2 Computer Socket**

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: ≥ 500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm × 86mm

A5 Come from the German that has long civilization and forerunner science and technology



A5G-TVPC

333.000 VND

Tivi & Computer Socket

TV :

1. Impedance: 75 Ω
2. Insertion Loss: VHF3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set

COMPUTER:

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500m\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm $\times$ 86mm


A5G-TELPC

333.000 VND

Telephone & Computer Socket

Telephone:

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500m\Omega$
3. Electrical Specification: ELA/TIABI

COMPUTER:

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500m\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm $\times$ 86mm


A5G-TVTEL

263.000 VND

Tivi & Telephone Socket

TV :

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set

Telephone:

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500m\Omega$
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm $\times$ 86mm


A5G-1D/J

796.000 VND

Insert Card for Power On

1. Working Voltage: 30A/220V
2. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm $\times$ 86mm


A5DPGK22

295.000 VND

2 Gang Switch
& with Please Clean
& Do not disturb

1. Working Voltage: 16A/250V
2. 1 Gang Please Clean Switch
3. 1 Gang Do not disturb Switch
4. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm $\times$ 86mm


A5G-3G/ML

578.000 VND

Don't Disturb & Please Clean
& Door bell Switch

1. Working Voltage: 220V ~ 50Hz
2. No Less than 500 M
3. Maximum load power 5A
4. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm $\times$ 86mm


A5G-1D/H

528.000 VND

Human Body Sensor Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Filament lamp 400W, fluorescent lamp,
Electronic fluorescent lamp 200W
3. Delay time: 30 ~ 40s
4. Static Power: < 0.6W
5. Light sensitive environment: Daybreak/Nightfall/Evening
6. Range: Level angle 120°C
7. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm $\times$ 86mm


A5ZDC

1.140.000 VND

Shaver Charging Socket

1. 10A ~ 16A
2. Load Power: 1100 ~ 2400W
3. Working Voltage: 110V ~ 220V
4. Plastics: PC - Box: 6 set - Carton: 60 set

Size:86mm $\times$ 86mm


A5G-1D/C

502.000 VND

Touch Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Current: 5A
3. Delay time: 30 $\pm$ 10s
4. Static Current $\leq 70\mu A$ (RMS)
5. Load Power: Filament lamp, Fluorescent lamps,
Electronic Fluorescent lamp
6. Plastics: PC - Box: 8 set - Carton: 80 set

Size:86mm $\times$ 86mm


A5A/S

535.000 VND

Step light

1. It is a light with sensor which you can install
in the stair or corridor.
2. This light is influenced by the ambient light sense,
and it will automatically sense the ambient light sense to
decide whether to turn it on or not.
3. Plastics: PC - Box: 10 set - Carton: 100 set

Size:86mm $\times$ 86mm

**A5G-1D/Y****362.000 VND**

Sound Control Switch

1. Signal frequency range: 100Hz ~ 20KHz
2. Rated load impedance: 8Ω
3. Rated input power: 5W
4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm

**A5G-1D/K****376.000 VND**

Sound Control Delay Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: Flamentlamp 400W, Fluorescent Lamps & LED Lamp 200W
3. Delay times: 60 ± 15s
4. Startic Power: < 0.6W
5. Sensifvity: 60 ~ 80db
6. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**SZ12/TEL/PC****980.000 VND**Floor Socket
& Pole Multi Function Socket

1. 16A/250V Floor Socket
2. 2x3 Pole multi Function Socket
3. Plastics: PC - Box: 1 set - Carton: 20 set

**S-2Z13/N****980.000 VND**Floor Socket
& Pole Multi Function Socket

1. 16A/250V Floor Socket
2. 2x3 Pole multi Function Socket
3. Plastics: PC - Box: 1 set - Carton: 20 set

**S-TEL/PC****980.000 VND**Floor Socket
& TEL Socket
& PC Socket

1. TEL Socket
2. PC Socket
3. Plastics: PC - Box: 1 set - Carton: 20 set

**S-Z13/PC****980.000 VND**Floor Socket
& Pole Multi Function Socket
& PC Socket

1. 16A/250V Floor Socket
2. Pole multi Function Socket
3. PC Socket
4. Plastics: PC - Box: 1 set - Carton: 20 set

**S-2Z13/N****980.000 VND**Floor Socket
& Pole Multi Function Socket

1. 16A/250V Table Socket
2. 2x3 Pole multi Function Socket
3. Plastics: PC - Box: 1 set - Carton: 20 set

**S-Z12/TEL/PC****980.000 VND**Floor Socket
2 Pole Socket
& TEL Socket & PC Socket

1. 2 Pole Socket
2. TEL Socket
3. PC Socket
4. Plastics: PC - Box: 1 set - Carton: 20 set

**UBIF/C****90.000 VND**

Waterproof Box

1. Waterproof
2. Plastics: PC - Box: 1 set - carton: 200 set

**UBBOX/A****24.000 VND**

Cassee Box

1. Plastics: PC - Carton: 100 set
- Size: 85mm × 85mm × 50mm

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



S300

Series

S300

Come from the German that has long civilization and forerunner science and technology



S300GK12

113.000 VND

1 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300GK22

137.000 VND

2 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300GK32

161.000 VND

3 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300GK42

186.000 VND

4 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300K11Z12Z13

177.000 VND

1 Gang 1 Way Switch
5 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300G-1G/M

120.000 VND

Door Bell Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300GK13

180.000 VND

1 Gang Multi Control Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300GK23

280.000 VND

2 Gang Multi Control Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300GZ13/2NU

513.000 VND

USB Charging & Universal Socket

1. 2.1A/ 5V USB Charging
 2. 16A/ 250V Universal Socket
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S300GZ12Z13/N

137.000 VND

5 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
 2. Copper Class: Phosphor Bronze
 3. Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

S300

Come from the German that has long civilization and forerunner science and technology



S300G-1TEL

146.000 VND

1 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



S300G-2TEL

177.000 VND

2 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



S300G-1TV

146.000 VND

1 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



S300G-2TV

177.000 VND

2 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



S300G-1PC

194.000 VND

1 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



S300G-2PC

265.000 VND

2 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



S300-TVTEL

177.000 VND

Tivi & Telephone

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm



S300-TVPC

230.000 VND

Tivi & Computer Socket

- TV :
1. Impedance: 75 Ω
 2. Insertion Loss: VHF3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
 1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
 - Size: 86mm $\times$ 86mm



S300-TELPC

230.000 VND

Telephone & Computer Socket

- Telephone:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
 - Size: 86mm $\times$ 86mm



S300-M/D

94.000 VND

Blank Panel

1. Blank Panel
2. Plastics: PC - Box: 20 set - Carton: 200 set
- Size: 86mm $\times$ 86mm

**S300GK20A****280.000 VND****20A Switch**

1. 20A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

**S300GK45A****340.000 VND****45A Switch**

1. 45A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

**S300ZDC****940.000 VND****Shaver Charging Socket**

1. 10A ~ 16A
 2. Load Power: 1100 ~ 2400W
 3. Working Voltage: 110V ~ 220V
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm

**S300G-1D/G****240.000 VND****Dimmer Control Switch**

1. Working Voltage: 220V ~ 50Hz
 2. Maximum load power: 500W
 3. Minimum Staring Voltage: 13~35V
 4. Only for filament Lamp
 5. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm

**S300G-1D/C****340.000 VND****Touch Delay Switch**

1. Working Voltage: 220V ~ 50Hz
 2. Current: 5A
 3. Delay time: 30 ± 10s
 4. Static Current: ≤ 70UA(RMS)
 5. Load Power: Filamentlamp, Fluorescentlamp, Electronic Fluorescentlamp
 6. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**S300G-1D/S****240.000 VND****Speed Control Switch**

1. Working Voltage: 220V ~ 50Hz
 2. Load Power: 25 ~ 300W
 3. Minimum Staring Voltage: 90~110V
 4. Load can be connected: Ceiling fan
 5. Never connect the zero line
 6. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm

**S300G-1D/J****580.000 VND****Insert Card for Power On**

1. Working Voltage: 30A/220V
 2. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm

S300G-1D/JG**970.000 VND****Insert Card for Power On(High frequency)**

1. Working Voltage: 30A/220V
 2. Only high-frequency card insert into it can get power/frequency: 13.56 MHz
 3. other card is useless on it
 6. Plastics: PC - Box: 6set - Carton: 60 set
- Size: 86mm × 86mm

**S300G-1D/F****591.000 VND****Electronic Airflow Switch**

1. Working Voltage: 220V ~ 50Hz
 2. Mximum load power: 5A
 3. Load Power: The motor
 4. Electronic Airflow Switch
 5. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**S300G-1D/H****390.000 VND****Human Body Sensor Switch**

1. Working Voltage: 220V ~ 50Hz
 2. Load Power: Filamentlamp 400W, fluorescentlamp, Electronic fluorescentlamp 200W
 3. Delay time: 30 ~ 40s
 4. Static Power: < 0.6W
 5. Light sensitive environment: Daybreak/Nightfall/Evening
 6. Range: Lebel angel 120°C
 7. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**S300G-1D/K****270.000 VND****Sound Control Delay Switch**

1. Working Voltage: 220V ~ 50Hz
 2. Load Power: Filamentlamp 400W, Fluorescent Lamps & LED Lamp 200W
 3. Delay times: 60 ± 15s
 4. Static Power: < 0.6W
 5. Sensifvity: 60 ~ 80db
 6. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

S300

Come from the German that has long civilization and forerunner science and technology



S300-A/S

480.000 VND

Step light

1. It is a light with sensor which you can install in the stair or corridor.
2. This light is influenced by the ambient light sense, and it will automatically sense the ambient light sense to decide whether to turn it on or not.
3. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm



S300G-3G/ML

570.000 VND

Don't Disturb & Please Clean & Door bell Switch

1. Working Voltage: 220V ~ 50Hz
2. No less than 500 MΩ
3. Maximum load power 5A
4. Plastics: PC - Box: 8 set - Carton: 80 set
Size: 86mm × 86mm



S300G-1STV

StatelliteTV Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm



S300G-2USB3.1

Double USB Charging

1. 2.1A/ 5V USB Charging
2. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm



S300-F/L

123.000 VND

SOS Emergency Socket

- Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm



S300-KZ13/N

180.000 VND

5 Pole Multi Function Socket

1. 16A/250VAC--50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C,
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm



S300-2KZ13/N

350.000 VND

5 Pole Multi Function Socket

1. 16A/250VAC--50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C,
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

UTEN

Noble and elegant,a symbol of nobles;
Fashionable and exquisite



S400

Series

S400

Come from the German that has long civilization and forerunner science and technology



S400GK12

113.000 VND

1 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GK22

137.000 VND

2 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GK32

161.000 VND

3 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GK42

186.000 VND

4 Gang 2 Way Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400K11Z12Z13

177.000 VND

1 Gang 1 Way Switch
5 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400G-1G/M

120.000 VND

Door Bell Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Switch Toggle: 40,000 times/Socket Toggle: 10,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GK13

180.000 VND

1 Gang Multi Control Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GK23

280.000 VND

2 Gang Multi Control Switch

1. 10A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 40,000 times
 4. Working Temperature: -20°C~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GZ13/2NU

513.000 VND

USB Charging & Universal Socket

1. 2.1A/ 5V USB Charging
 2. 16A/ 250V Universal Socket
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GZ12Z13/N

137.000 VND

5 Pole Multi Function Socket

1. 16A/250VAC -- 50/60Hz
 2. Copper Class: Phosphor Bronze
 3. Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm

**S400G-1TEL****146.000 VND**

1 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm

**S400G-2TEL****177.000 VND**

2 Telephone Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm

**S400G-1TV****146.000 VND**

1 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm

**S400-2TV****177.000 VND**

2 Tivi Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm

**S400G-1PC****194.000 VND**

1 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm

**S400G-2PC****265.000 VND**

2 Computer Socket

1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm

**S400-TVTEL****177.000 VND**

Tivi & Computer Socket

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm $\times$ 86mm

**S400-TVPC****230.000 VND**

Tivi & Computer Socket

- TV :
1. Impedance: 75 Ω
 2. Insertion Loss: VHF3.5dB
UHF < 5dB, Flatness in band ± 1.0 dB
 3. Plastics: PC - Box: 10 set - Carton: 100 set
- COMPUTER:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
 - Size: 86mm $\times$ 86mm

**S400-TELPC****230.000 VND**

Telephone & Computer Socket

- Telephone:
1. Temperature: -20 ~ 70°C
 2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
1. Temperature: -20 ~ 70°C
2. Insertion Resistance: $\geq 500\text{m}\Omega$
 3. Electrical Specification: ELA/TIABI
 4. Connection Mode: T568A, T568B
 5. Plastics: PC - Box: 10 set - Carton: 100 set
 - Size: 86mm $\times$ 86mm

**S400-M/D****94.000 VND**

Blank Panel

1. Blank Panel
2. Plastics: PC - Box: 20 set - Carton: 200 set
- Size: 86mm $\times$ 86mm

S400

Come from the German that has long civilization and forerunner science and technology



S400GK20A

290.000 VND

20A Switch

1. 20A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400GK45A

340.000 VND

45A Switch

1. 45A/250VAC -- 50/60Hz
 2. Contact Point: Silver 0.35mm - Purple Copper: 65% Cu
 3. Switch Structure: Seesaw - Toggle: 10,000 times
 4. Working Temperature: -20°C ~ 70°C.
 5. Plastics: PC - Box: 10 set - Carton: 100 set
- Size: 86mm × 86mm



S400ZDC

940.000 VND

Shaver Charging Socket

1. 10A ~ 16A
 2. Load Power: 1100 ~ 2400W
 3. Working Voltage: 110V ~ 220V
 4. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm



S400-1D/G

240.000 VND

Dimmer Control Switch

1. Working Voltage: 220V ~ 50Hz
 2. Maximum load power: 500W
 3. Minimum Starting Voltage: 13~35V
 4. Only for filament Lamp
 5. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm



S400-3G/ML

570.000 VND

Don't Disturb & Please Clean
& Door bell Switch

1. Working Voltage: 220V ~ 50Hz
 2. No less than 500 MΩ
 3. Maximum load power 5A
 4. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm



S400G-1D/S

240.000 VND

Speed Control Switch

1. Working Voltage: 220V ~ 50Hz
 2. Load Power: 25 ~ 300W
 3. Minimum Starting Voltage: 90~110V
 4. Load can be connected: Ceiling fan
 5. Never connect the zero line
 6. Plastics: PC - Box: 8 set - Carton: 60 set
- Size: 86mm × 86mm



S400G-1D/J

580.000 VND

Insert Card for Power On

1. Working Voltage: 30A/220V
 2. Plastics: PC - Box: 6 set - Carton: 60 set
- Size: 86mm × 86mm

S400G-1D/JG

970.000 VND

Insert Card for Power On(High frequency)

1. Working Voltage: 30A/220V
 2. Only high-frequency card insert into it can get power/frequency:13.56 MHz
 3. other card is useless on it
 6. Plastics: PC - Box: 6set - Carton: 60 set
- Size: 86mm × 86mm



S400G-1D/C

340.000 VND

Touch Delay Switch

1. Working Voltage: 220V ~ 50Hz
 2. Current: 5A
 3. Delay time: 30 ± 10s
 4. Staric Current ≤ 70UA(RMS)
 5. Load Power: Filamentlamp, Fluoresce Ntlamps, Electronic Fluorescentlamp
 6. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm



S400-1D/H

390.000 VND

Human Body Sensor Switch

1. Working Voltage: 220V ~ 50Hz
 2. Load Power: Filamentlamp 400W, fluorescentlamp, Electronic fluorescentlamp 200W
 3. Delay time: 30 ~ 40s
 4. Static Power: < 0.6W
 5. Light sensitive environment: Daybreak/Nightfall/Evening
 6. Range: Lebel angel 120°C
 7. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm



S400G-1D/K

270.000 VND

Sound Control Delay Switch

1. Working Voltage: 220V ~ 50Hz
 2. Load Power: Flamentlamp 400W, Fluorescent Lamps & LED Lamp 200W
 3. Delay times: 60 ± 15s
 4. Staric Power: < 0.6W
 5. Sensitivity: 60 ~ 80db
 6. Plastics: PC - Box: 8 set - Carton: 80 set
- Size: 86mm × 86mm

**S400-A/S****480.000 VND****Step light**

1. It is a light with sensor which you can install in the stair or corridor.
2. This light is influenced by the ambient light sense, and it will automatically sense the ambient light sense to decide whether to turn it on or not.
3. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

**S400G-1D/F****890.000 VND****Electronic Airflow Switch**

1. Working Voltage: 220V ~ 50Hz
2. Maximum load power: 5A
3. Load Power: The motor
4. Electronic Airflow Switch
5. Plastics: PC - Box: 8 set - Carton: 80 set
Size: 86mm × 86mm

**S400-1TV****SatellliteTV Socket**

1. Impedance: 75 Ω
2. Insertion Loss: VHF < 3.5dB
UHF < 5dB, Flatness in band ±1.0 dB
3. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

**S400G-2USB3.1****Double USB Charging**

1. 2.1A/ 5V USB Charging
2. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

**S400-F/L****SOS Emergency Socket**

- Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

**S400-KZ13/N****180.000 VND****5 Pole Multi Function Socket**

1. 16A/250VAC--50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C,
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

**S400-2KZ13/N****350.000 VND****5 Pole Multi Function Socket**

1. 16A/250VAC--50/60Hz
2. Copper Class: Phosphor Bronze
3. Toggle: 10,000 times
4. Working Temperature: -20°C ~ 70°C,
5. Plastics: PC - Box: 10 set - Carton: 100 set
Size: 86mm × 86mm

Noble and elegant,a symbol of nobles;
Fashionable and exquisite

Gold

Z9
Series

UTEN



Z9

Come from the German that has long civilization and forerunner science and technology



Z9GK12

430.000 VND

1 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GK22

612.000 VND

2 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GK32

792.000 VND

3 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GK42

980.000 VND

4 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9MD

388.000 VND

Blank Panel

- 1.Blank Panel
- 2.Glass-box:20 sets- Carton:200 sets
- 4.Size:86mm×86mm



Z9G-1GM

446.000 VND

Door Bell Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GK13

612.000 VND

1 Gang Multi Control Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GK23

830.000 VND

2 Gang Multi Control Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GK20A

710.000 VND

20A Switch

- 1.20A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GK45A

830.000 VND

45A Switch

- 1.45A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm

Z9

Come from the German that has long civilization and forerunner science and technology



Z9GZ/S

690.000 VND

Schuko Socket

- 1.16A /250VAC- 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Toggle:10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GZ12Z13/N

548.000 VND

5 Pole Multi Function Socket

- 1.16A /250VAC- 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Toggle:10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9GKZ12Z13/N

730.000 VND

5 Pole Multi Function Socket With Switch

- 1.16A /250VAC- 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times/ Socket Toggle:10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9G-1TEL

548.000 VND

1 Telephone Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Glass- box:10 sets- Carton:100 sets
- Size:86mm×86mm



Z9G-2TEL

712.000 VND

2 Telephone Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Glass- box:10 sets- Carton:100 sets
- 5.Size:86mm×86mm



Z9G-1TV

548.000 VND

1 TV Socket

- 1.Impedance:75Ω
- 2.Insertion Loss:VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB
- 3.Glass- box:10 sets- Carton:100 sets
- 4.Size:86mm×86mm



Z9G-2TV

712.000 VND

2 TV Socket

- 1.Impedance:75Ω
- 2.Insertion Loss:VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB
- 3.Glass- box:10 sets- Carton:100 sets
- 4.Size:86mm×86mm



Z9G-1PC

676.000 VND

1 Computer Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Connection Mode: T568A,T568B
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9G-2PC

938.000 VND

2 Computer Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Connection Mode: T568A,T568B
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm



Z9TVTEL

676.000 VND

TV& Telephone Socket

- TV:
- 1.Impedance:75Ω
 - 2.Insertion Loss:VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB
- Telephone Socket:
- 1.Working Temperature:-20°C ~ 70°C
 - 2.Insertion Resistance:≥500mΩ
 - 3.Electrical Specification:ELA/TIABI
 - 4.Glass- box:10 sets- Carton:100 sets
 - 5.Size:86mm×86mm

**Z9TVPC****770.000 VND****TV & Computer Socket****TV:**

1. Impedance: 75Ω
2. Insertion Loss: VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB

Computer:

1. Working Temperature: -20°C ~ 70°C
2. Insertion Resistance: ≥500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Glass- box: 10 sets- Carton: 100 sets
6. Size: 86mm×86mm

**Z9TELPC****770.000 VND****Telephone & Computer Socket****Telephone Socket:**

1. Working Temperature: -20°C ~ 70°C
2. Insertion Resistance: ≥500mΩ
3. Electrical Specification: ELA/TIABI

Computer:

1. Working Temperature: -20°C ~ 70°C
2. Insertion Resistance: ≥500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Glass- box: 10 sets- Carton: 100 sets
6. Size: 86mm×86mm

**Z9GZ13/2NU****1.600.000 VND****3 Pole Universal Socket with Double USB**

1. 2.1A/5V USB Charging
2. 16A/250V Universal Socket
3. Glass- box: 10 sets- Carton: 100 sets
4. Size: 86mm×86mm

**Z9G-1D/G****876.000 VND****Dimmer Control Switch**

1. Working Voltage: 220V ~ 50Hz
2. Maximum Load Power: 500W
3. Minimum Starting Voltage: 13V ~ 35V
4. Only for filament Lamp
5. Glass- box: 8 sets- Carton: 80 sets
6. Size: 86mm×86mm

**Z9G-1D/S****876.000 VND****Speed Control Switch**

1. Working Voltage: 220V ~ 50Hz
2. Load Power: 25 ~ 300W
3. Minimum Starting Voltage: 90V ~ 110V
4. Load can be connected: Ceiling Fan
5. Never connect the zero line
6. Glass- box: 8 sets- Carton: 80 sets
7. Size: 86mm×86mm

**Z9G-1D/Y****972.000 VND****Sound Control Switch**

1. Signal frequency range: 100Hz ~ 20kHz
2. Rated Load impedance: 8Ω
3. Rated Input Power: 5W
5. Glass- box: 8 sets- Carton: 80 sets
6. Size: 86mm×86mm

**Z9ZDC****2.865.000 VND****Shaver Charging Socket**

1. 10A ~ 16A
2. Load Power: 1100W ~ 2400W
3. Working Voltage: 110V ~ 220V
4. Glass- box: 7 sets- Carton: 70 sets
5. Size: 86mm×86mm

**Z9G-3G/ML****1.680.000 VND****Don't Disturb & Please Clean & Door bell Switch**

1. Working Voltage: 220V ~ 50Hz
2. No Less than 500mΩ
3. Maximum Load Power: 5A
5. Glass- box: 8 sets- Carton: 80 sets
6. Size: 86mm×86mm

**Z9DPGK22****810.000 VND****2 Gang Switch & Please Clean & Do not Disturb**

1. Working Voltage: 16A/250V
2. 1 Gang Please Clean Switch
3. 1 Gang Do not Disturb Switch
4. Glass- box: 10 sets- Carton: 100 sets
5. Size: 86mm×86mm

**Z9G-1D/J****2.732.000 VND****Insert Card for Power On**

1. Working Voltage: 30A/220V
2. Glass- box: 10 sets- Carton: 100 sets
3. Size: 86mm×86mm
4. Glass- box: 8 sets- Carton: 80 sets
5. Size: 86mm×86mm

Z9

Come from the German that has long civilization and forerunner science and technology



Z9G-1D/JG

3.332.000 VND

Insert Card for Power On(High frequency)

- 1.Working Voltage:30A/220V
- 2.Only High-Frequency card insert into it can get power/Frequency:13.56MHz
- 3.Other Card is useless on it
- 4.Glass- box:8 sets- Carton:80 sets
- 5.Size:86mm×86mm



Z9G-1D/H

1.780.000 VND

Human Body Sensor Switch

- 1.Working Voltage:220V ~ 50Hz
- 2.Load Power: Filament Lamp 400W, Fluorescent Lamp, Electronic Fluorescent Lamp 200W
- 3.Delay time:30 ~ 40s
- 4.Static Power: < 0.6W
- 5.Light sensitive environment:Daybreak/Nightfall/Evening
- 6.Range:Label angel 120°
- 7.Glass- box:8 sets- Carton:80 sets
- 8.Size:86mm×86mm



Z9G-1D/C

1.468.000 VND

Touch Delay Switch

- 1.Working Voltage:220V ~ 50Hz
- 2.Current:5A
- 3.Delay time : 30±10s
- 4.Static Currents:70UA(RMS)
- 5.Load Power: Filament Lamp, Fluorescent Lamp, Electronic Fluorescent Lamp
- 6.Glass- box:8 sets- Carton:80 sets
- 7.Size:86mm×86mm



Z9KZ13/N

1.500.000 VND

13A Single Socket with Switch+ USB

- 1.13A/250VAC- 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Toggle: 10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:8 sets- Carton:80 sets
- 6.Size:86mm×86mm



Noble and elegant,a symbol of nobles;
Fashionable and exquisite

Gray

Z9
Series

Z9

Come from the German that has long civilization and forerunner science and technology


Z9GK12
430.000 VND

1 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9GK22
612.000 VND

2 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9GK32
792.000 VND

3 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9GK42
980.000 VND

4 Gang 2 Way Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9MD
388.000 VND

Blank Panel

- 1.Blank Panel
- 2.Glass-box:20 sets- Carton:200 sets
- 4.Size:86mm×86mm


Z9G-1GM
446.000 VND

Door Bell Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9GK13
612.000 VND

1 Gang Multi Control Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9GK23
830.000 VND

2 Gang Multi Control Switch LED

- 1.10A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9GK20A
710.000 VND

20A Switch

- 1.20A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm


Z9GK45A
830.000 VND

45A Switch

- 1.45A/250VAC- 50/60Hz
- 2.Contact Point: Silver 0.35mm- Purple Copper:65% Cu
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm

**Z9GZ/S****690.000 VND**

Schuko Socket

- 1.16A /250VAC- 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Toggle:10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm

**Z9GZ12Z13/N****548.000 VND**

5 Pole Multi Function Socket

- 1.16A /250VAC- 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Toggle:10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm

**Z9GKZ12Z13/N****730.000 VND**

5 Pole Multi Function Socket With Switch

- 1.16A /250VAC- 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Switch Structure:Seesaw- Switch Toggle:40,000 times/ Socket Toggle:10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm

**Z9G-1TEL****548.000 VND**

1 Telephone Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Glass- box:10 sets- Carton:100 sets
- Size:86mm×86mm

**Z9G-2TEL****712.000 VND**

2 Telephone Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Glass- box:10 sets- Carton:100 sets
- 5.Size:86mm×86mm

**Z9G-1TV****548.000 VND**

1 TV Socket

- 1.Lmpedance:75Ω
- 2.Insertion Loss:VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB
- 3.Glass- box:10 sets- Carton:100 sets
- 4.Size:86mm×86mm

**Z9G-2TV****712.000 VND**

2 TV Socket

- 1.Lmpedance:75Ω
- 2.Insertion Loss:VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB
- 3.Glass- box:10 sets- Carton:100 sets
- 4.Size:86mm×86mm

**Z9G-1PC****676.000 VND**

1 Computer Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Connection Mode: T568A, T568B
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm

**Z9G-2PC****938.000 VND**

2 Computer Socket

- 1.Working Temperature:-20°C ~ 70°C
- 2.Insertion Resistance:≥500mΩ
- 3.Electrical Specification:ELA/TIABI
- 4.Connection Mode: T568A, T568B
- 5.Glass- box:10 sets- Carton:100 sets
- 6.Size:86mm×86mm

**Z9TVTEL****676.000 VND**

TV & Telephone Socket

- TV:
- 1.Lmpedance:75Ω
 - 2.Insertion Loss:VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB
- Telephone Socket:
- 1.Working Temperature:-20°C ~ 70°C
 - 2.Insertion Resistance:≥500mΩ
 - 3.Electrical Specification:ELA/TIABI
 - 4.Glass- box:10 sets- Carton:100 sets
 - 5.Size:86mm×86mm

Z9

Come from the German that has long civilization and forerunner science and technology



Z9TVPC

770.000 VND

TV & Computer Socket

TV:

1. Impedance: 75Ω
2. Insertion Loss: VHF < 3.5dB, UHF < 5dB, Flatness in band ±1.0dB

Computer:

1. Working Temperature: -20°C ~ 70°C
2. Insertion Resistance: ≥500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Glass- box: 10 sets- Carton: 100 sets
6. Size: 86mm×86mm



Z9TELPC

770.000 VND

Telephone & Computer Socket

Telephone Socket:

1. Working Temperature: -20°C ~ 70°C
2. Insertion Resistance: ≥500mΩ
3. Electrical Specification: ELA/TIABI

Computer:

1. Working Temperature: -20°C ~ 70°C
2. Insertion Resistance: ≥500mΩ
3. Electrical Specification: ELA/TIABI
4. Connection Mode: T568A, T568B
5. Glass- box: 10 sets- Carton: 100 sets
6. Size: 86mm×86mm



Z9GZ13/2NU

1.600.000 VND

3 Pole Universal Socket with Double USB

1. 2.1A/5V USB Charging
2. 16A/250V Universal Socket
3. Glass- box: 10 sets- Carton: 100 sets
4. Size: 86mm×86mm



Z9G-1D/G

876.000 VND

Dimmer Control Switch

1. Working Voltage: 220V ~ 50Hz
2. Maximum Load Power: 500W
3. Minimum Starting Voltage: 13V ~ 35V
4. Only for filament Lamp
5. Glass- box: 8 sets- Carton: 80 sets
6. Size: 86mm×86mm



Z9G-1D/S

876.000 VND

Speed Control Switch

1. Working Voltage: 220V ~ 50Hz
2. Load Power: 25 ~ 300W
3. Minimum Starting Voltage: 90V ~ 110V
4. Load can be connected: Ceiling Fan
5. Never connect the zero line
6. Glass- box: 8 sets- Carton: 80 sets
7. Size: 86mm×86mm



Z9G-1D/Y

972.000 VND

Sound Control Switch

1. Signal frequency range: 100Hz ~ 20kHz
2. Rated Load impedance: 8Ω
3. Rated Input Power: 5W
5. Glass- box: 8 sets- Carton: 80 sets
6. Size: 86mm×86mm



Z9ZDC

2.865.000 VND

Shaver Charging Socket

1. 10A ~ 16A
2. Load Power: 1100W ~ 2400W
3. Working Voltage: 110V ~ 220V
4. Glass- box: 7 sets- Carton: 70 sets
5. Size: 86mm×86mm



Z9G-3G/ML

1.680.000 VND

Don't Disturb & Please Clean & Door bell Switch

1. Working Voltage: 220V ~ 50Hz
2. No Less than 500mΩ
3. Maximum Load Power: 5A
5. Glass- box: 8 sets- Carton: 80 sets
6. Size: 86mm×86mm



Z9DPGK22

810.000 VND

2 Gang Switch & Please Clean & Do not Disturb

1. Working Voltage: 16A/250V
2. 1 Gang Please Clean Switch
3. 1 Gang Do not Disturb Switch
4. Glass- box: 10 sets- Carton: 100 sets
5. Size: 86mm×86mm



Z9G-1D/J

2.732.000 VND

Insert Card for Power On

1. Working Voltage: 30A/220V
2. Glass- box: 10 sets- Carton: 100 sets
3. Size: 86mm×86mm
4. Glass- box: 8 sets- Carton: 80 sets
5. Size: 86mm×86mm


Z9G-1D/JG 3.332.000 VND

insert Card for Power On(High frequency)

- 1.Working Voltage:30A/220V
- 2.Only High-Frequency card insert into it can get power/Frequency:13.56MHz
- 3.Other Card is useless on it
- 4.Glass- box:8 sets- Carton:80 sets
- 5.Size:86mm×86mm


Z9G-1D/H 1.780.000 VND

Human Body Sensor Switch

- 1.Working Voltage:220V ~ 50Hz
- 2.Load Power: Filament Lamp 400W, Fluorescent Lamp, Electronic Fluorescent Lamp 200W
- 3.Delay time:30 ~ 40s
- 4.Static Power: < 0.6W
- 5.Light sensitive environment:Daybreak/Nightfall/Evening
- 6.Range:Label angel 120°
- 7.Glass- box:8 sets- Carton:80 sets
- 8.Size:86mm×86mm


Z9G-1D/C 1.468.000 VND


Touch Delay Switch

- 1.Working Voltage:220V ~ 50Hz
- 2.Current:5A
- 3.Delay time : 30±10s
- 4.Static Currents70UA(RMS)
- 5.Load Power: Filament Lamp, Fluorescent Lamp, Electronic Fluorescent Lamp
- 6.Glass- box:8 sets- Carton:80 sets
- 7.Size:86mm×86mm


Z9KZ13/N 1.500.000 VND


13A Single Socket with Switch+ USB

- 1.13A/250VAC - 50/60Hz
- 2.Copper Class:Phosphor Bronze
- 3.Toggle: 10,000 times
- 4.Working Temperature:-20°C ~ 70°C
- 5.Glass- box:8 sets- Carton:80 sets
- 6.Size:86mm×86mm


Z9-M/2M 89.000 VND


Double Panel with bracket

Plastics: PC
Size:147mm × 90mm


Z9-M/3M 129.000 VND


Triple Panel with bracket

Plastics: PC
Size:260mm × 90mm


Z9-M/4M 169.000 VND

Quadruple Panel with bracket

Size:346mm × 90mm


Z9-M/5M 219.000 VND

Quintuple Panel with bracket

Size:432mm × 90mm



M5-A104T 435,000^{VND}

Circuit Breakers Box, 2P - 4P

1. Size: 140x170x15,5 (mm) Cut: 118x150x90(mm)
2. Material: ABS fireproof plastic, transparent window
3. Box is Powder coated metal



M5-A107T 750,000^{VND}

Circuit Breakers Box, 5P - 7P

1. Size: 224x240x15,5 (mm) Cut: 202x210x90(mm)
2. Material: ABS fireproof plastic, transparent window
3. Box is Powder coated metal



M5-A110T 885,000^{VND}

Circuit Breakers Box, 8P - 10P

1. Size: 278x240x15,5 (mm) Cut: 256x210x90(mm)
2. Material: ABS fireproof plastic, transparent window
3. Box is Powder coated metal



M5-A112T 980,000^{VND}

Circuit Breakers Box, 10P - 12P

1. Size: 316x240x15,5 (mm) Cut: 292x210x90(mm)
2. Material: ABS fireproof plastic, transparent window
3. Box is Powder coated metal



M5-A115T 995,000^{VND}

Circuit Breakers Box, 13P - 15P

1. Size: 370x240x15,5 (mm) Cut: 346x220x90(mm)
2. Material: ABS fireproof plastic, transparent window
3. Box is Powder coated metal



M5-A118T 1,150,000^{VND}

Circuit Breakers Box, 16P - 18P

1. Size: 424x260x15,5 (mm) Cut: 400x220x90(mm)
2. Material: ABS fireproof plastic, transparent window
3. Box is Powder coated metal



M5-A224T 2,595,000^{VND}

Circuit Breakers Box, 20P - 24P

1. Size: 335x460x19 (mm) Cut: 305x420x90(mm)
2. Material: ABS fireproof plastic, transparent window
3. Box is Powder coated metal



M5-A104M 435,000^{VND}

Circuit Breakers Box, 2P - 4P

1. Size: 140x170x15,5 (mm) Cut: 118x150x90(mm)
2. Material: ABS fireproof plastic, coated window
3. Box is Powder coated metal



M5-A107M 750,000^{VND}

Circuit Breakers Box, 5P - 7P

1. Size: 224x240x15,5 (mm) Cut: 202x210x90(mm)
2. Material: ABS fireproof plastic, coated window
3. Box is Powder coated metal



M5-A110M 885,000^{VND}

Circuit Breakers Box, 8P - 10P

1. Size: 278x240x15,5 (mm) Cut: 256x210x90(mm)
2. Material: ABS fireproof plastic, coated window
3. Box is Powder coated metal



M5-A112M 980,000^{VND}

Circuit Breakers Box, 10P - 12P

1. Size: 316x240x15,5 (mm) Cut: 292x210x90(mm)
2. Material: ABS fireproof plastic, coated window
3. Box is Powder coated metal



M5-A115M 995,000^{VND}

Circuit Breakers Box, 13P - 15P

1. Size: 370x240x15,5 (mm) Cut: 346x220x90(mm)
2. Material: ABS fireproof plastic, coated window
3. Box is Powder coated metal



M5-A118M 1,150,000^{VND}

Circuit Breakers Box, 16P - 18P

1. Size: 424x260x15,5 (mm) Cut: 400x220x90(mm)
2. Material: ABS fireproof plastic, coated window
3. Box is Powder coated metal



M5-A224M 2,595,000^{VND}

Circuit Breakers Box, 20P - 24P

1. Size: 335x460x19 (mm) Cut: 305x420x90(mm)
2. Material: ABS fireproof plastic, coated window
3. Box is Powder coated metal



MCB 1P 6kA 400V C curve



Code	I_n	Price
N8BH1P10A	10A	122,000 ^{VND}
N8BH1P16A	16A	122,000 ^{VND}
N8BH1P20A	20A	122,000 ^{VND}
N8BH1P25A	25A	122,000 ^{VND}
N8BH1P32A	32A	122,000 ^{VND}
N8BH1P40A	40A	182,000 ^{VND}
N8BH1P50A	50A	182,000 ^{VND}

RCCB 30mA 240-415V AC type



Code	I_n	Price
N8LGM2P25A	25A	1,029,000 ^{VND}
N8LGM2P32A	32A	1,080,000 ^{VND}
N8LGM2P40A	40A	1,159,000 ^{VND}
N8LGM2P63A	63A	1,357,000 ^{VND}

MCB 2P 6kA 400V C curve



Code	I_n	Price
N8BH2P20A	20A	378,000 ^{VND}
N8BH2P25A	25A	378,000 ^{VND}
N8BH2P32A	32A	378,000 ^{VND}
N8BH2P40A	40A	378,000 ^{VND}
N8BH2P50A	50A	655,000 ^{VND}
N8BH2P63A	63A	655,000 ^{VND}
$I_{cu} = 10kA$		
N8GH2P80A	80A	1,210,000 ^{VND}

RCBO 1P + N 6kA 30mA



Code	I_n	Price
SL6N1PN10A	10A	895,000 ^{VND}
SL6N1PN16A	16A	895,000 ^{VND}
SL6N1PN20A	20A	895,000 ^{VND}
SL6N1PN25A	25A	895,000 ^{VND}
SL6N1PN32A	32A	895,000 ^{VND}
SL6N1PN25A	40A	895,000 ^{VND}
SL6N1PN25A	50A	895,000 ^{VND}
SL6N1PN25A	63A	895,000 ^{VND}

MCB 3P 6kA 230/400V C curve



Code	I_n	Price
N8BH3P25A	25A	910,000 ^{VND}
N8BH3P32A	32A	910,000 ^{VND}
N8BH3P40A	40A	1,018,000 ^{VND}
N8BH3P50A	50A	1,018,000 ^{VND}
N8BH3P63A	63A	1,018,000 ^{VND}
$I_{cu} = 10kA$		
N8GH3P80A	80A	2,015,000 ^{VND}
N8GH3P100A	100A	2,015,000 ^{VND}

MCCB 3P 25kA 410/415V



Code	I_n	Price
EM125N3P25A	25A	2,159,000 ^{VND}
EM125N3P32A	32A	2,159,000 ^{VND}
EM125N3P40A	40A	2,159,000 ^{VND}
EM125N3P50A	50A	2,159,000 ^{VND}
EM125N3P63A	63A	2,159,000 ^{VND}
EM125N3P80A	80A	2,159,000 ^{VND}
EM125N3P100A	100A	2,159,000 ^{VND}
EM125N3P125A	125A	2,439,000 ^{VND}

VIET-DUC UTEN JOIN STOCK COMPANY